Avenue EcoBase SoundMaster Lite

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424	Tufted 1/10 "					
Aspect	ISO 2424		Structured loop pile				
Dye method			Solution dyed				
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68" x 19,68" (16 tiles per box)				
Primary backing	ISO 2424		Polyester fleece				
Secondary backing	ISO 2424		EcoBase SoundMaster Lite, contains on average 75% recycled content.				
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **				
Total thickness	ISO 1765	mm	10.0	inch	0.4		
Effective pile thickness	ISO 1766	mm	5.0	inch	0.20		
Total mass	ISO 8543	g/m²	4450	oz/yd²	131.3		
Total pile mass	ISO 2424	g/m²	840	oz/yd²	24.8		
Effective pile mass	ISO 8543	g/m²	610	oz/yd²	18.0		
Pile density	ISO 8543	g/cm³	0.122	lb/in³	0.0044		
Number of tufts	ISO 1763	/dm²	1580	/yd²	132104		
Stroll test	ISO 6356	kV	≤ 2,0				
Vertical resistance	ISO 10965	Ohm	-				
Horizontal resistance	ISO 10965	Ohm	-				
Use classification	EN 1307		33 Commercial - heavy use				
Luxury rating	EN 1307		LC 3				
Dimensional stability	EN 986	%	≤ 0,2				
Impact sound reduction ΔL_w	ISO 10140	dB	35				
Sound absorption	ISO 354	Freq. Hz	125 25	0 500	1000	2000	4000
		α _s	0.00 0.0	0.30	0.25	0.30	0.35
Noise reduction	ISO 354	α _w	0.30				
Thermal resistance	ISO 8302	m².K/W	0.131				
Flammability	EN 13501-1		Cfl - s1 (loose laid tested)				
Prodis - GUT	www.pro-dis.info)	0CC3A1BA				





* DESSO EcoBase[®] is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle[®] assessment criteria. As described in Cradle to Cradle[®] Certified CM Product Standard Version 3.1. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com For products with acoustic backing: SoundMaster/SoundMaster Lite backings contain 80% recycled polyester felt, SoundMaster Thrive is a low antimony polyester felt.

** ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

EN-20240220

Tarkett BV Taxandriaweg 15 NL-5142 PA Waalwijk

