

## Eclectic EcoBase SoundMaster Lite

Preliminary specification according to EN 1307

Type of manufacture	ISO 2424		Tufted 1/10 "					
Aspect	ISO 2424		Structured loop pile					
Dye method			Solution dye	d				
Dimension	EN ISO 24342	cm x cm	50 x 50 / 19,68" x 19,68" (16 tiles per box)					
Primary backing	ISO 2424		Polyester fleece					
Secondary backing	ISO 2424		EcoBase SoundMaster Lite, contains on average 75% recycled content.					
Pile fibre composition	ISO 2424		BCF Polyamide 6 ECONYL® (ECONYL® is made from 100% regenerated content) **					
Total thickness	ISO 1765	mm	10.0	inch	0.4			
Effective pile thickness	ISO 1766	mm	5.0	inch	0.20			
Total mass	ISO 8543	g/m²	4450	oz/yd²	131.3			
Total pile mass	ISO 2424	g/m²	840	oz/yd²	24.8			
Effective pile mass	ISO 8543	g/m²	610	oz/yd²	18.0			
Pile density	ISO 8543	g/cm³	0.122	lb/in³	0.0044			
Number of tufts	ISO 1763	/dm²	1580	/yd²	132104			
Stroll test	ISO 6356	kV	≤ 2,0					
Vertical resistance	ISO 10965	Ohm	-					
Horizontal resistance	ISO 10965	Ohm	-					
Use classification	EN 1307		33 Commercial - heavy use					
Luxury rating	EN 1307		LC 3					
Dimensional stability	EN 986	%	≤ 0,2					
Impact sound reduction $\Delta L_{_W}$	ISO 10140	dB	35					
Sound absorption	ISO 354	Freq. Hz	125 25	0 500	1000	2000	4000	
		$\alpha_s$	0.00 0.0	0.30	0.25	0.30	0.35	
Noise reduction	ISO 354	$\alpha_{w}$	0.30					
Thermal resistance	ISO 8302	m².K/W	0.131					
Flammability	EN 13501-1		Cfl - s1 (loose laid tested)					
<u> </u>		www.pro-dis.info						





- \* DESSO EcoBase® is a polyolefin based backing. Positively defined means: all ingredients have been assessed as either Green (optimal) or Yellow (tolerable) according to the Cradle to Cradle® assessment criteria. As described in Cradle to Cradle® Certified CM Product Standard Version 3.1. The total % of recycled content varies per product and per colour which can be found on our website: www.tarkett.com For products with acoustic backing: SoundMaster/SoundMaster Lite backings contain 80% recycled polyester felt, SoundMaster Thrive is a low antimony polyester felt.
- \*\* ECONYL® is a yarn made from 100% regenerated content. The total % of regenerated content varies per product and per colour. Whether a colour contains ECONYL® and the exact % thereof can be found on our website: www.tarkett.com

DESSO flooring products are to be installed in full accordance with Tarkett's installation instructions and recognized trade standards. An effective, regular cleaning and maintenance program is vital for retaining a high appearance level. DESSO flooring products should only be used as floorcoverings. Note: Tarkett reserves the right to change this specification without prior notice; changes are subject to normal production tolerances. For the latest versions of the technical specifications, visit www.tarkett.com

**O** Tarkett